

Вентилятор воздуходувки

Home / All Products / [Вентилятор воздуходувки](#)

Вентилятор воздуходувки

General Data
UF160DPB Series
UF90DPB Series

Product Application:

Features: Fulltech's blowers are with the same motor design as centrifugal fan, the blowing direction will be more corcus and stronger.

Product Application:

- Cooling fan for electrical box
- Cooling fan for ventilation system
- Cooling fan for ventilation in tunnel working environment
- Cooling fan for ventilation in house

General Data : [File Download](#)

Frame/Housing:	Aluminum die-casting
Impeller:	Plastic or steel
Bearing System:	Ball bearing
Motor:	Shaded pole or capacitor start-run
Protection:	Impedance-Protected or Thermally-Protected or Electronically-Protected
Insulation Resistance:	Above 100MΩ, DC500V.
Dielectric withstand voltage	AC 1,500V (50/60Hz) one minute
Life Expectancy:	Ball bearing: Over 40,000 hr. (at 40°C)
Safety Approval:	CUL, CE, TUV, either UL or ETL.
Description of Model No.	UF220APA11H1C2A 1 2 3 4 5 6 7 8 9 10

1.Model Series:

UF:Fulltech

2.Blade Diameter:

- Option 1). E
- E: EC Motor
- Option 2). Blank
- 133(72):133mm(72mm Thick)
- 133(91):133mm(91mm Thick)
- 175: 175mm
- 180: 180mm
- 180(55):180mm(55mm Thick)
- 190: 190mm
- 220: 220mm
- 225(99):225mm(99mm Thick)
- 225(85):225mm(85mm Thick)
- 225(69):225mm(69mm Thick)
- 250: 250mm
- 318: 318mm
- 300: 300mm
- 360: 360mm
- 400: 400mm
- 12A: Ø112*38mm
- 15P: Ø145*51mm

3.Sort of Fan:

- A: Centrifugal Fan
- B: Axial Fan
- D: Blower Fan

4.Sort of Blade:

- A: Aluminum
- P: Plastic
- M: Welded Steel
- N: Pressed Steel

5.Air Check:

Centrifugal Fan

- A: Backward Curve, Single Air Intake.
- B: Forward Curve, Single Air Intake.
- C: Forward Curve, Dual Air Intake.

Axial Fan

- A: Air Discharge Out of Rotor Side
- B: Air Discharge Opposite Rotor Side

Blower Fan

- B: Forward Single Air Inlet
- C: Forward Dual Air Inlet

6.Voltage:

- 11: 115V
- 23: 230V
- 38: 380V
- OA:115V-230V

7.Speed:

- H1: High
- M1: Medium
- L1: Low

8.Sort of Motor

- A: 3 Phases
- S: Shaded Pole
- C: Capacitor Run Motor
- D: Single Phase EC Motor

9.Poles of Motor

- 2: 2P
- 4: 4P
- 6: 6P

10.Special Requirement

Axial Fan

- A: Standard with Frame
- E: Without Frame
- B: With Low Guard / No Frame
- C: With High Guard / No Frame
- D: With Guard & Duct

Centrifugal Fan

- A: Standard
- F: With Mounting Disk

Product Size: